

Description

grip range: 0.094" - 0.156", diameter: 0.164", general purpose, protruding head internally threaded, external sleeve, NAS1669 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS166908L2 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-00-550-4792 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N NAS1669-08L2 Specifications

| | |
|-------------------------------------|--|
| Fastener Length: | 0.215 Inches Minimum And 0.245 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.096 Inches Nominal |
| Shank Diameter: | 0.162 Inches Minimum And 0.164 Inches Maximum |
| Shank Style: | Threaded Self-plugging Shank W/sleeve |
| Expansion Device: | Threaded Stem |
| Grip Length: | 0.094 Inches Minimum And 0.156 Inches Maximum |
| Width Across Flats: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Material: | Steel Body |
| Material: | Steel Corrosion Resisting Sleeve |
| Material: | Steel Stem |
| Surface Treatment: | Cadmium Overall |
| Specification/standard Data: | 80205-nas1669 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1669-08L2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.