

**Description**

grip range: 0.22" - 0.281", diameter: 0.164", general purpose rivet, protruding head internally threaded, external sleeve, NAS1669 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS166908L4
Minimum Qty (MOQ):	10
NSN:	5320-00-550-4791
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1669-08L4 Specifications

<b>Fastener Length:</b>	0.340 Inches Minimum And 0.370 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.096 Inches Nominal
<b>Shank Diameter:</b>	0.162 Inches Minimum And 0.164 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Expansion Device:</b>	Threaded Stem
<b>Grip Length:</b>	0.220 Inches Minimum And 0.281 Inches Maximum
<b>Width Across Flats:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Material:</b>	Steel Body
<b>Material:</b>	Steel Corrosion Resisting Sleeve
<b>Material:</b>	Steel Stem
<b>Surface Treatment:</b>	Cadmium Overall
<b>Specification/standard Data:</b>	80205-nas1669 Professional/Industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1669-08L4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.