

P/N NAS1669-08L9

Military-Fasteners.com

Description

grip range: 0.532" - 0.594", diameter: 0.164", general purpose blind rivet, protruding head internally threaded, external sleeve

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | NAS166908L9 |
|-------------------------|---|
| Minimum Qty (MOQ): | 5 |
| NSN: | 5320-00-983-9847 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



P/N NAS1669-08L9 Specifications

| Fastener Length: | 0.653 Inches Minimum And 0.683 Inches Maximum |
|---|--|
| Head Style: | Hexagon |
| Head Height: | 0.096 Inches Nominal |
| Shank Diameter: | 0.162 Inches Minimum And 0.164 Inches Maximum |
| Expansion Device: | Threaded Stem |
| Grip Length: | 0.532 Inches Minimum And 0.594 Inches Maximum |
| Width Across Flats: | 0.244 Inches Minimum And 0.250 Inches Maximum |
| Hardness Rating: | 39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt |
| Hardness Rating: | 39.0 Rockwell C Minimum Nut And 43.0 Rockwell C Maximum Nut |
| Material: | Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt |
| Material: | Steel Comp 4140 Nut Or Steel Comp 8740 Nut Or Steel Comp 4130 Nut |
| Material: | Steel Comp 304 Sleeve Or Steel Comp 303f Sleeve Or Steel Comp 303 Sleeve |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Bolt |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Nut Or Mil-s-6049 Mil Spec 2nd Material Response Nut Or Mil-s-6758 Mil Spec 3rd Material Response Nut |
| Material Document And Classification: | Qq-s-763 Fed Spec 1st Material Response Sleeve Or Ams 5639 Assn Std 1st Material Response Sleeve Or Ams 5641 Assn Std 2nd Material Response Sleeve Or Astm A582 Assn Std 3rd Material Response Sleeve |
| Surface Treatment: | Cadmium Bolt And Chromate Bolt |
| Surface Treatment: | Cadmium Nut And Chromate Nut |
| Surface Treatment: | Cadmium Sleeve And Passivate Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416,ty 1,cl 3 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Nut |
| Specification/standard Data: | 80205-nas1669 Professional/industrial Association Standard |
| | |

How to Order

Order this blind rivet from our inventory online by visiting <u>https://military-fasteners.com/rivets/blind+rivets/NAS1669-08L9</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.