

Description

grip range: 0.094" - 0.156", diameter: 0.200", general purpose blind rivet, protruding head internally threaded, external sleeve

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS16693L2 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5320-01-305-0605 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N NAS1669-3L2 Specifications

| | |
|--|---|
| Shank Diameter: | 0.1970 Inches Minimum And 0.1990 Inches Maximum |
| Features Provided: | Drive Nut |
| Material: | Steel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303se Sleeve |
| Material: | Steel Comp 4130 Nut Or Steel Comp 4140 Nut Or Steel Comp 8740 Nut |
| Material Document And Classification: | Astm A582 Assn Std 1st Material Response Sleeve Or Ams 5639 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve |
| Material Document And Classification: | Mil-s-6758 Mil Spec 1st Material Response Nut Or Mil-s-5626 Mil Spec 2nd Material Response Nut Or Mil-s-6049 Mil Spec 3rd Material Response Nut |
| Surface Treatment: | Cadmium Bolt And Chromate Bolt |
| Surface Treatment: | Cadmium Nut And Chromate Nut |
| Surface Treatment: | Passivate Sleeve And Cadmium Sleeve |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec 1st Treatment Response Sleeve And Qq-p-416,ty1,cl3 Fed Spec 2nd Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Nut |
| Specification/standard Data: | 80205-nas1669 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1669-3L2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.