

# P/N NAS1669-3L5

### **Description**

grip range: 0.282" - 0.344", diameter: 0.200", general purpose blind rivet, protruding head internally threaded, external sleeve

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

| SKU / Model:       | NAS16693L5       |
|--------------------|------------------|
| Minimum Qty (MOQ): | 5                |
| NSN:               | 5320-00-068-9987 |
| ECCN:              | EAR99            |



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1669-3L5 Specifications

| Head Style:                                    | Hexagon   |
|--|---|
| Head Height:                                   | 0.113 Inches Maximum  |
| Shank Diameter:                                | 0.1970 Inches Minimum And 0.1990 Inches Maximum   |
| Shank Style:                                   | Threaded Self-plugging Shank W/sleeve   |
| Expansion Device:                              | Threaded Stem   |
| Grip Length:                                   | 0.282 Inches Minimum And 0.344 Inches Maximum   |
| Width Across Flats:                            | 0.305 Inches Minimum And 0.312 Inches Maximum   |
| Material:                                      | Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 303se Boltsteel Comp 4140 Nut Or Steel Comp 8740 Nut Or Steel Comp 303se Nutsteel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303se Sleeve  |
| Material Document And Classification:          | Mil-s-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Boltmil-s-5626 Mil Spec 1st Material Response Nut Or Mil-s-6049 Mil Spec 2nd Material Response Nut Or Mil-s-6758 Mil Spec 3rd Material Response Nutqq-s-763 Fed Spec 1st Material Response Sleeve Or Ams 5639 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve |
| Surface Treatment:                             | Cadmium Bolt And Chromate Boltcadmium Nut And Chromate Nutpassivate Sleeve And Cadmium Sleeve   |
| Surface Treatment Document And Classification: | Qq-p-416 Ty li Cl 2 Fed Spec Single Treatment Response Boltqq-p-416 Ty li Cl 2 Fed Spec Single Treatment Response Nutmil-s-5002 Mil Spec 1st Treatment Response Sleeve And Qq-p-416 Ty l Cl 3 Fed Spec 2nd Treatment Response Sleeve  |

## **How to Order**

Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1669-3L5">https://military-fasteners.com/rivets/blind+rivets/NAS1669-3L5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1669-3L5">https://military-fasteners.com/rivets/blind+rivets/NAS1669-3L5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1669-3L5">https://military-fasteners.com/rivets/blind+rivets/NAS1669-3L5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/rivets/NAS1669-3L5">https://military-fasteners.com/rivets/blind+rivets/NAS1669-3L5</a> and selecting the quantity you want then