

**Description**

grip range: 0.220" - 0.281", diameter: 0.260", general purpose blind rivet - protruding head internally threaded - external sleeve with drive nut

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS16694DL4
Minimum Qty (MOQ):	1
NSN:	5320-01-306-1552
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N NAS1669-4DL4 Specifications

<b>Shank Diameter:</b>	0.2580 Inches Minimum And 0.2600 Inches Maximum
<b>Features Provided:</b>	Drive Nut
<b>Material:</b>	Steel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303se Sleeve
<b>Material:</b>	Steel Comp 4130 Nut Or Steel Comp 4140 Nut Or Steel Comp 8740 Nut
<b>Material Document And Classification:</b>	Astm A582 Assn Std 1st Material Response Sleeve Or Ams 5639 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve
<b>Material Document And Classification:</b>	Mil-s-6758 Mil Spec 1st Material Response Nut Or Mil-s-5626 Mil Spec 2nd Material Response Nut Or Mil-s-6049 Mil Spec 3rd Material Response Nut
<b>Surface Treatment:</b>	Cadmium Bolt And Chromate Bolt
<b>Surface Treatment:</b>	Cadmium Nut And Chromate Nut
<b>Surface Treatment:</b>	Passivate Sleeve And Cadmium Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec 1st Treatment Response Sleeve And Qq-p-416,ty1,cl3 Fed Spec 2nd Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Nut
<b>Specification/standard Data:</b>	80205-nas1669 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1669-4DL4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.