

Description

grip range: 0.094" - 0.156", diameter: 0.260", general purpose, protruding head internally threaded, external sleeve, jo bolt, NAS1669 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS16694L2
Minimum Qty (MOQ):	5
NSN:	5320-01-543-6821
Schedule B:	7318.15.8085
ECCN:	EAR99



P/N NAS1669-4L2 Specifications

Fastener Length:	0.447 Inches Nominal
Head Style:	Hexagon
Head Height:	0.135 Inches Maximum
Shank Diameter:	0.2580 Inches Minimum And 0.2600 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Expansion Device:	Break Stem
Grip Length:	0.094 Inches Minimum And 0.156 Inches Maximum
Width Across Flats:	0.367 Inches Minimum And 0.375 Inches Maximum
Material:	Steel Comp 4130 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Specification/standard Data:	80205-has1669 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1669-4L2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.