

**Description**

grip range: 0.094" - 0.156", diameter: 0.260", general purpose, protruding head internally threaded, external sleeve, jo bolt, NAS1669 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS16694L2
Minimum Qty (MOQ):	5
NSN:	5320-01-543-6821
Schedule B:	7318.15.8085
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS1669-4L2 Specifications

<b>Fastener Length:</b>	0.447 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.135 Inches Maximum
<b>Shank Diameter:</b>	0.2580 Inches Minimum And 0.2600 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Expansion Device:</b>	Break Stem
<b>Grip Length:</b>	0.094 Inches Minimum And 0.156 Inches Maximum
<b>Width Across Flats:</b>	0.367 Inches Minimum And 0.375 Inches Maximum
<b>Material:</b>	Steel Comp 4130 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-6758 Mil Spec 1st Material Response Overall Or Mil-s-5626 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Specification/standard Data:</b>	80205-has1669 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1669-4L2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.