

P/N NAS1669-4L3

Description

grip range: 0.157" - 0.219", diameter: 0.260", general purpose, protruding head internally threaded, external sleeve, jo bolt, NAS1669 series rivet

Order this part online

Additional Information

Minimum Qty (MOQ): 5

NSN: 5320-00-209-1980

Schedule B: 7318.15.8085

ECCN: EAR99









^{*} Manufacturer certifications are shipped with your order FREE of charge

P/N NAS1669-4L3 Specifications

Head Style:	Hexagon
Head Height:	0.135 Inches Maximum
Shank Diameter:	0.2580 Inches Minimum And 0.2600 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Expansion Device:	Threaded Stem
Grip Length:	0.157 Inches Minimum And 0.219 Inches Maximum
Width Across Flats:	0.367 Inches Minimum And 0.375 Inches Maximum
Material:	Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 303se Boltsteel Comp 4140 Nut Or Steel Comp 8740 Nut Or Steel Comp 303se Nutsteel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303se Sleeve
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Boltmil-s-5626 Mil Spec 1st Material Response Nut Or Mil-s-6049 Mil Spec 2nd Material Response Nut Or Mil-s-6758 Mil Spec 3rd Material Response Nutqq-s-763 Fed Spec 1st Material Response Sleeve Or Ams 5639 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve
Surface Treatment:	Cadmium Bolt And Chromate Boltcadmium Nut And Chromate Nutpassivate Sleeve And Cadmium Sleeve
Surface Treatment Document And Classification:	Qq-p-416 Ty li Cl 2 Fed Spec Single Treatment Response Boltqq-p-416 Ty li Cl 2 Fed Spec Single Treatment Response Nutmil-s-5002 Mil Spec 1st Treatment Response Sleeve And Qq-p-416 Ty l Cl 3 Fed Spec 2nd Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting https://military-fasteners.com/rivets/blind+rivets/NAS1669-4L3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/NAS1669-4L3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/NAS1669-4L3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/rivets/blind+rivets/NAS1669-4L3 and selecting the quantity you want then