

Description

grip range: 0.220" - 0.281", diameter: 0.260", general purpose, protruding head internally threaded, external sleeve, NAS1669 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS16694L4
Minimum Qty (MOQ):	5
NSN:	5320-00-539-5749
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N NAS1669-4L4 Specifications

Fastener Length:	0.281 Inches Nominal
Head Style:	Hexagon
Head Height:	0.135 Inches Nominal
Shank Diameter:	0.258 Inches Minimum And 0.260 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Expansion Device:	Threaded Mandrel
Grip Length:	0.220 Inches Minimum And 0.281 Inches Maximum
Width Across Flats:	0.367 Inches Minimum And 0.375 Inches Maximum
Material:	Steel Body
Material:	Steel Corrosion Resisting Sleeve
Material:	Steel Stem
Surface Treatment:	Cadmium Overall
Specification/standard Data:	80205-nas1669 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1669-4L4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.