

**Description**

grip range: 0.282" - 0.344", diameter: 0.26", general purpose, protruding head, internally threaded, external sleeve, NAS1669 series rivet

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS16694L5
Minimum Qty (MOQ):	5
NSN:	5320-00-637-5044
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N NAS1669-4L5 Specifications

<b>Fastener Length:</b>	0.429 Inches Minimum And 0.459 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.135 Inches Nominal
<b>Shank Diameter:</b>	0.258 Inches Minimum And 0.260 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Expansion Device:</b>	Threaded Stem
<b>Grip Length:</b>	0.282 Inches Minimum And 0.344 Inches Maximum
<b>Width Across Flats:</b>	0.367 Inches Minimum And 0.375 Inches Maximum
<b>Material:</b>	Steel Body
<b>Material:</b>	Steel Corrosion Resisting Sleeve
<b>Material:</b>	Steel Stem
<b>Surface Treatment:</b>	Cadmium Overall
<b>Specification/standard Data:</b>	80205-nas1669 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1669-4L5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.