

Description

grip range: 0.345" - 0.406", diameter: 0.260", general purpose, protruding head internally threaded, external sleeve, jo bolt, NAS1669 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS16694L6 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5320-00-558-3431 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N NAS1669-4L6 Specifications

| | |
|-------------------------------------|---|
| Fastener Length: | 0.491 Inches Minimum And 0.521 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.135 Inches Nominal |
| Shank Diameter: | 0.258 Inches Minimum And 0.260 Inches Maximum |
| Shank Style: | Threaded Self-plugging Shank W/sleeve |
| Expansion Device: | Threaded Mandrel |
| Grip Length: | 0.345 Inches Minimum And 0.406 Inches Maximum |
| Width Across Flats: | 0.367 Inches Minimum And 0.375 Inches Maximum |
| Hardness Rating: | 39.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall |
| Shear Strength: | 9000 Double Pounds Per Square Inch |
| Material: | Steel Body |
| Material: | Steel Corrosion Resisting Sleeve |
| Material: | Steel Stem |
| Surface Treatment: | Cadmium Overall |
| Specification/standard Data: | 80205-nas1669 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1669-4L6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.