

**Description**

Head Width: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS16695DL14
Minimum Qty (MOQ):	5
NSN:	5320-01-339-1981
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1669-5DL14 Specifications

<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.160 Inches Maximum
<b>Shank Diameter:</b>	0.3095 Inches Minimum And 0.3115 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Expansion Device:</b>	Break Stem
<b>Grip Length:</b>	0.845 Inches Minimum And 0.906 Inches Maximum
<b>Width Across Flats:</b>	0.429 Inches Minimum And 0.437 Inches Maximum
<b>Features Provided:</b>	Drive Nut
<b>Special Features:</b>	Drive Nut Mild Steel Color Gold With Corrosion Retardent Coating
<b>Material:</b>	Steel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303se Sleeve
<b>Material:</b>	Steel Comp 4130 Bolt Or Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt
<b>Material:</b>	Steel Comp 4130 Nut Or Steel Comp 4140 Nut Or Steel Comp 8740 Nut
<b>Material Document And Classification:</b>	Astm A582 Assn Std 1st Material Response Sleeve Or Ams 5639 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve
<b>Material Document And Classification:</b>	Mil-s-6758 Mil Spec 1st Material Response Bolt Or Mil-s-5626 Mil Spec 2nd Material Response Bolt Or Mil-s-6049 Mil Spec 3rd Material Response Bolt
<b>Material Document And Classification:</b>	Mil-s-6758 Mil Spec 1st Material Response Nut Or Mil-s-5626 Mil Spec 2nd Material Response Nut Or Mil-s-6049 Mil Spec 3rd Material Response Nut
<b>Surface Treatment:</b>	Cadmium Bolt And Chromate Bolt
<b>Surface Treatment:</b>	Cadmium Nut And Chromate Nut
<b>Surface Treatment:</b>	Passivate Sleeve And Cadmium Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec 1st Treatment Response Sleeve And Qq-p-416,ty1,cl3 Fed Spec 2nd Treatment Response Sleeve
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Bolt
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Nut
<b>Specification/standard Data:</b>	80205-nas1669 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1669-5DL14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.