

**Description**

Fastener Length: 1/4", Head Width: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS16695L2
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-550-4790
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N NAS1669-5L2 Specifications

<b>Fastener Length:</b>	0.266 Inches Minimum And 0.296 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.160 Inches Maximum
<b>Shank Diameter:</b>	0.309 Inches Minimum And 0.311 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Expansion Device:</b>	Threaded Stem
<b>Grip Length:</b>	0.094 Inches Minimum And 0.156 Inches Maximum
<b>Width Across Flats:</b>	0.429 Inches Minimum And 0.437 Inches Maximum
<b>Material:</b>	Steel Body
<b>Material:</b>	Steel Corrosion Resisting Sleeve
<b>Material:</b>	Steel Stem
<b>Surface Treatment:</b>	Cadmium Overall
<b>Specification/standard Data:</b>	80205-nas1669 Professional/industrial Association Standard

## How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1669-5L2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.