

Description

Fastener Length: 1/4", Head Width: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS16695L2
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-550-4790
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N NAS1669-5L2 Specifications

Fastener Length:	0.266 Inches Minimum And 0.296 Inches Maximum
Head Style:	Hexagon
Head Height:	0.160 Inches Maximum
Shank Diameter:	0.309 Inches Minimum And 0.311 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Expansion Device:	Threaded Stem
Grip Length:	0.094 Inches Minimum And 0.156 Inches Maximum
Width Across Flats:	0.429 Inches Minimum And 0.437 Inches Maximum
Material:	Steel Body
Material:	Steel Corrosion Resisting Sleeve
Material:	Steel Stem
Surface Treatment:	Cadmium Overall
Specification/standard Data:	80205-nas1669 Professional/industrial Association Standard

How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1669-5L2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.