

Description

Head Width: 1/2

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | NAS16696DL4 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5320-01-340-6750 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



* See page 2 for technical characteristics

P/N NAS1669-6DL4 Specifications

| | |
|-------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Head Style: | Hexagon |
| Head Height: | 0.190 Inches Maximum |
| Shank Diameter: | 0.3730 Inches Minimum And 0.3750 Inches Maximum |
| Shank Style: | Threaded Self-plugging Shank W/sleeve |
| Expansion Device: | Break Stem |
| Grip Length: | 0.220 Inches Minimum And 0.281 Inches Maximum |
| Width Across Flats: | 0.491 Inches Minimum And 0.500 Inches Maximum |
| Features Provided: | Drive Nut |
| Special Features: | Drive Nut Mild Steel Color Gold With Corrosion Retardent Coating |
| Material: | Steel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303se Sleeve |
| Material: | Steel Comp 4130 Bolt Or Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt |
| Material: | Steel Comp 4130 Nut Or Steel Comp 4140 Nut Or Steel Comp 8740 Nut |
| Material Document And Classification: | Astm A582 Assn Std 1st Material Response Sleeve Or Ams 5639 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve |
| Material Document And Classification: | Mil-s-6758 Mil Spec 1st Material Response Bolt Or Mil-s-5626 Mil Spec 2nd Material Response Bolt Or Mil-s-6049 Mil Spec 3rd Material Response Bolt |
| Material Document And Classification: | Mil-s-6758 Mil Spec 1st Material Response Nut Or Mil-s-5626 Mil Spec 2nd Material Response Nut Or Mil-s-6049 Mil Spec 3rd Material Response Nut |
| Surface Treatment: | Cadmium Bolt And Chromate Bolt |
| Surface Treatment: | Cadmium Nut And Chromate Nut |
| Surface Treatment: | Passivate Sleeve And Cadmium Sleeve |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec 1st Treatment Response Sleeve And Qq-p-416,ty1,cl3 Fed Spec 2nd Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Bolt |
| Surface Treatment Document And Classification: | Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Nut |
| Specification/standard Data: | 80205-nas1669 Professional/industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1669-6DL4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.