

# P/N NAS1669-6L5

# **Description**

Fastener Length: 35/64", Head Width: 1/2", Jo bolt, NAS1669 series rivet

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

# Order this part online

### **Additional Information**

SKU / Model: NAS16696L5

Minimum Qty (MOQ): 5

NSN: 5320-00-772-1342

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc









# P/N NAS1669-6L5 Specifications

Fastener Length:	0.527 Inches Minimum And 0.557 Inches Maximum
Head Style:	Hexagon
Head Height:	0.180 Inches Minimum And 0.190 Inches Maximum
Shank Diameter:	0.373 Inches Minimum And 0.375 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Expansion Device:	Threaded Stem
Lubrication:	Wax Or Dry Film
Grip Length:	0.281 Inches Minimum And 0.344 Inches Maximum
Width Across Flats:	0.491 Inches Minimum And 0.500 Inches Maximum
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Shear Strength:	19500 Double Pounds Per Square Inch
Special Features:	Self-locking
Heat Treatment:	Annealed Overall
Material:	Steel Comp 303f Sleeve
Material:	Steel Comp 4130 Stem Or Steel Comp 8740 Stem Or Steel Comp 4140 Stem
Material:	Steel Comp 4130 Body Or Steel Comp 8740 Body Or Steel Comp 4140 Body
Material Document And Classification:	Ams 5641 Assn Std Single Material Response Sleeve
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Body Or Mil-s-6049 Mil Spec 2nd Material Response Body Or Mil-s-5626 Mil Spec 3rd Material Response Body
Material Document And Classification:	Mil-s-6758 Mil Spec 1st Material Response Stem Or Mil-s-6049 Mil Spec 2nd Material Response Stem Or Mil-s-5626 Mil Spec 3rd Material Response Stem
Surface Treatment:	Cadmium Body
Surface Treatment:	Cadmium Sleeve
Surface Treatment:	Cadmium Stem
Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response Sleeve
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Body
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Stem
Specification/standard Data:	80205-nas1669 Professional/industrial Association Standard

# **How to Order** Order this blind rivet from our inventory online by visiting <a href="https://military-fasteners.com/rivets/blind+rivets/NAS1669-6L5">https://military-fasteners.com/rivets/blind+rivets/NAS1669-6L5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order. Provided by Military-Fasteners.com