

Description

Fastener Length: 23/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS167008L10
Minimum Qty (MOQ):	1 EA
NSN:	5320-00-800-6192
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1670-08L10 Specifications

Fastener Length:	0.715 Inches Minimum And 0.745 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.163 Inches Minimum And 0.165 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Head Major Diameter:	0.325 Inches Minimum And 0.332 Inches Maximum
Expansion Device:	Threaded Stem
Grip Length:	0.595 Inches Minimum And 0.656 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Self-locking
Material:	Steel Body
Material:	Steel Corrosion Resisting Sleeve
Material:	Steel Stem
Surface Treatment:	Cadmium Overall
Specification/standard Data:	80205-nas1670 Professional/industrial Association Standard

How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1670-08L10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.