

Description

grip range: 0.094" - 0.156", diameter: 0.164", general purpose, flush head, internally threaded, external sleeve, NAS1670 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS167008L2 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5320-00-550-2213 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N NAS1670-08L2 Specifications

| | |
|-----------------------------|--|
| Fastener Length: | 0.215 Inches Minimum And 0.245 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.163 Inches Minimum And 0.165 Inches Maximum |
| Head Major Diameter: | 0.325 Inches Minimum And 0.332 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.094 Inches Minimum And 0.156 Inches Maximum |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Body |
| Material: | Steel Corrosion Resisting Sleeve |
| Material: | Steel Stem |
| Surface Treatment: | Cadmium Overall |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1670-08L2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.