

Description

grip range: 0.282" - 0.344", diameter: 0.164", general purpose rivet, flush head, internally threaded, external sleeve, NAS1670 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS167008L5
Minimum Qty (MOQ):	10
NSN:	5320-01-407-6237
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N NAS1670-08L5 Specifications

Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.1625 Inches Minimum And 0.1645 Inches Maximum
Head Major Diameter:	0.325 Inches Minimum And 0.332 Inches Maximum
Expansion Device:	Knob Stem-type K
Grip Length:	0.282 Inches Minimum And 0.344 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4140 Nut
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall
Material:	Steel Comp 304 Sleeve
Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Nut
Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Overall
Material Document And Classification:	Qq-s-763 Fed Spec Single Material Response Sleeve
Surface Treatment:	Cadmium Overall And Chromate Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1670-08L5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.