

**Description**

grip range: 0.094" - 0.156", diameter: 0.200", general purpose blind rivet, flush head, internally threaded, external sleeve

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS16703L2
Minimum Qty (MOQ):	5
NSN:	5320-00-205-7473
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N NAS1670-3L2 Specifications

<b>Fastener Length:</b>	0.213 Inches Minimum And 0.243 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.197 Inches Minimum And 0.199 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Head Major Diameter:</b>	0.342 Inches Minimum And 0.385 Inches Maximum
<b>Expansion Device:</b>	Threaded Stem
<b>Grip Length:</b>	0.094 Inches Minimum And 0.156 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Bolt Or Steel Corrosion Resisting Bolt
<b>Material:</b>	Steel Nut Or Steel Corrosion Resisting Nut
<b>Material:</b>	Steel Sleeve Or Steel Corrosion Resisting Sleeve
<b>Surface Treatment:</b>	Cadmium Bolt
<b>Surface Treatment:</b>	Cadmium Nut
<b>Surface Treatment:</b>	Cadmium Sleeve
<b>Specification/standard Data:</b>	80205-nas1670 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1670-3L2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.