



Military-Fasteners.com

P/N NAS1670-3L2

Description

grip range: 0.094" - 0.156", diameter: 0.200", general purpose blind rivet, flush head, internally threaded, external sleeve

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS16703L2
Minimum Qty (MOQ):	5
NSN:	5320-00-205-7473
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1670-3L2 Specifications

Fastener Length:	0.213 Inches Minimum And 0.243 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.197 Inches Minimum And 0.199 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Head Major Diameter:	0.342 Inches Minimum And 0.385 Inches Maximum
Expansion Device:	Threaded Stem
Grip Length:	0.094 Inches Minimum And 0.156 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Bolt Or Steel Corrosion Resisting Bolt
Material:	Steel Nut Or Steel Corrosion Resisting Nut
Material:	Steel Sleeve Or Steel Corrosion Resisting Sleeve
Surface Treatment:	Cadmium Bolt
Surface Treatment:	Cadmium Nut
Surface Treatment:	Cadmium Sleeve
Specification/standard Data:	80205-nas1670 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1670-3L2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.