

Description

grip range: 0.220" - 0.281", diameter: 0.200", general purpose, flush head, internally threaded, external sleeve, NAS1670 series rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS16703L4
Minimum Qty (MOQ):	10
NSN:	5320-00-637-6115
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N NAS1670-3L4 Specifications

Fastener Length:	0.338 Inches Minimum And 0.368 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.197 Inches Minimum And 0.199 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Head Major Diameter:	0.378 Inches Minimum And 0.385 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.220 Inches Minimum And 0.281 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Body
Material:	Steel Corrosion Resisting Sleeve
Material:	Steel Stem
Surface Treatment:	Cadmium Overall

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1670-3L4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.