

**Description**

grip range: 0.282" - 0.344", diameter: 0.200", general purpose blind rivet, flush head, internally threaded, external sleeve

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                             |
|-------------------------|---------------------------------------------|
| SKU / Model:            | NAS16703L5                                  |
| Minimum Qty (MOQ):      | 10                                          |
| NSN:                    | 5320-00-205-7792                            |
| ECCN:                   | EAR99                                       |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

## P/N NAS1670-3L5 Specifications

|                             |                                                                                |
|-----------------------------|--------------------------------------------------------------------------------|
| <b>Fastener Length:</b>     | 0.401 Inches Minimum And 0.431 Inches Maximum                                  |
| <b>Head Style:</b>          | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>      | 0.197 Inches Minimum And 0.199 Inches Maximum                                  |
| <b>Shank Style:</b>         | Threaded Self-plugging Shank W/sleeve                                          |
| <b>Head Major Diameter:</b> | 0.378 Inches Minimum And 0.385 Inches Maximum                                  |
| <b>Expansion Device:</b>    | Serrated Stem-type W                                                           |
| <b>Grip Length:</b>         | 0.282 Inches Minimum And 0.344 Inches Maximum                                  |
| <b>Countersink Angle:</b>   | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                 |
| <b>Material:</b>            | Steel Overall Or Steel Corrosion Resisting Overall                             |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1670-3L5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.