

## Description

grip range: 0.407" - 0.469", diameter: 0.200", general purpose blind rivet - flush head - internally threaded - external sleeve "

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS16703L7                                  |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5320-00-732-1428                            |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



\* See page 2 for technical characteristics

## P/N NAS1670-3L7 Specifications

|                             |  |
|-----------------------------|--|
| <b>Fastener Length:</b>     | 0.526 Inches Minimum And 0.556 Inches Maximum                                  |
| <b>Head Style:</b>          | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| <b>Shank Diameter:</b>      | 0.197 Inches Minimum And 0.199 Inches Maximum                                  |
| <b>Shank Style:</b>         | Threaded Self-plugging Shank W/sleeve  |
| <b>Head Major Diameter:</b> | 0.378 Inches Minimum And 0.385 Inches Maximum                                  |
| <b>Expansion Device:</b>    | Serrated Stem-type W   |
| <b>Grip Length:</b>         | 0.407 Inches Minimum And 0.469 Inches Maximum                                  |
| <b>Countersink Angle:</b>   | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                 |
| <b>Material:</b>            | Steel Body   |
| <b>Material:</b>            | Steel Corrosion Resisting Sleeve   |
| <b>Material:</b>            | Steel Stem   |
| <b>Surface Treatment:</b>   | Cadmium Overall  |

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1670-3L7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.