

Description

grip range: 0.470" - 0.531", diameter: 0.200", general purpose blind rivet - flush head - internally threaded - external sleeve

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---------------------------------------------|
| SKU / Model: | NAS16703L8 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5320-00-728-3729 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N NAS1670-3L8 Specifications

| | |
|-------------------------------------|--------------------------------------------------------------------------------|
| Fastener Length: | 0.588 Inches Minimum And 0.618 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.197 Inches Minimum And 0.199 Inches Maximum |
| Shank Style: | Threaded Self-plugging Shank W/sleeve |
| Head Major Diameter: | 0.378 Inches Minimum And 0.385 Inches Maximum |
| Expansion Device: | Threaded Mandrel |
| Grip Length: | 0.470 Inches Minimum And 0.531 Inches Maximum |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Body |
| Material: | Steel Corrosion Resisting Sleeve |
| Material: | Steel Stem |
| Surface Treatment: | Cadmium Overall |
| Specification/standard Data: | 80205-nas1670 Professional/Industrial Association Standard |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1670-3L8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.