

Description

Fastener Length: 29/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS16704L5 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5320-00-732-1431 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 096320, Rivets I / S Nickel Plated Buffed |



* See page 2 for technical characteristics

P/N NAS1670-4L5 Specifications

| | |
|---|--|
| Fastener Length: | 0.429 Inches Minimum And 0.459 Inches Maximum |
| Head Style: | Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer) |
| Shank Diameter: | 0.258 Inches Minimum And 0.507 Inches Maximum |
| Head Major Diameter: | 0.499 Inches Minimum And 0.507 Inches Maximum |
| Expansion Device: | Serrated Stem-type W |
| Grip Length: | 0.282 Inches Nominal |
| Hardness Rating: | 39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt |
| Hardness Rating: | 39.0 Rockwell C Minimum Nut And 43.0 Rockwell C Maximum Nut |
| Countersink Angle: | 101.0 Degrees Nominal |
| Material: | Steel Comp 303 Sleeve Or Steel Comp 304 Sleeve Or Steel Comp 303f Sleeve |
| Material: | Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt |
| Material: | Steel Comp 4140 Nut Or Steel Comp 8740 Nut Or Steel Comp 4130 Nut |
| Material Document And Classification: | Astm A582 Assn Std 1st Material Response Sleeve Or Qq-s-763 Fed Spec All Material Responses Sleeve Or Ams 5639 Assn Std 2nd Material Response Sleeve Or Ams 6541 Assn Std 3rd Material Response Sleeve |
| Material Document And Classification: | Mil-s-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Bolt |
| Material Document And Classification: | Mil-s-5627 Mil Spec 1st Material Response Nut Or Mil-s-6049 Mil Spec 2nd Material Response Nut Or Mil-s-6758 Mil Spec 3rd Material Response Nut |
| Surface Treatment: | Cadmium Bolt And Chromate Bolt |
| Surface Treatment: | Cadmium Nut And Chromate Nut |
| Surface Treatment: | Cadmium Sleeve And Chromate Sleeve |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec 1st Treatment Response Sleeve And Qq-p-416 Ty1 Cl3 Fed Spec 2nd Treatment Response Sleeve |
| Surface Treatment Document And Classification: | Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Bolt |
| Surface Treatment Document And Classification: | Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Nut |

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1670-4L5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.