

Description

Fastener Length: 37/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS16704L7
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-205-7868
Schedule B:	7318.15.8085
ECCN:	9A991



NO IMAGE
AVAILABLE

P/N NAS1670-4L7 Specifications

Fastener Length:	0.554 Inches Minimum And 0.584 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.258 Inches Minimum And 0.260 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Head Major Diameter:	0.499 Inches Minimum And 0.507 Inches Maximum
Expansion Device:	Serrated Stem-type W
Grip Length:	0.407 Inches Minimum And 0.469 Inches Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Corrosion Resisting Body
Material:	Steel Sleeve
Material:	Steel Stem
Surface Treatment:	Cadmium Overall

How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1670-4L7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.