

## Description

Fastener Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS16706L6
Minimum Qty (MOQ):	1
NSN:	5320-00-819-8717
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1670-6L6 Specifications

<b>Fastener Length:</b>	0.589 Inches Minimum And 0.619 Inches Maximum
<b>Head Style:</b>	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
<b>Shank Diameter:</b>	0.373 Inches Minimum And 0.375 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Head Major Diameter:</b>	0.752 Inches Minimum And 0.762 Inches Maximum
<b>Expansion Device:</b>	Threaded Mandrel
<b>Grip Length:</b>	0.345 Inches Minimum And 0.406 Inches Maximum
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Body
<b>Material:</b>	Steel Corrosion Resisting Sleeve
<b>Material:</b>	Steel Stem
<b>Surface Treatment:</b>	Cadmium Overall
<b>Specification/standard Data:</b>	80205-nas1670 Professional/industrial Association Standard

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1670-6L6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.