

Description


Head Width: 1/4", Jo-bolt, NAS1671 series

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS167108L3
Minimum Qty (MOQ):	5
NSN:	5320-00-820-7283
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



P/N NAS1671-08L3 Specifications

Head Style:	Hexagon
Head Height:	0.096 Inches Maximum
Shank Diameter:	0.1625 Inches Minimum And 0.1645 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Expansion Device:	Threaded Stem
Lubrication:	Wax Or Cetyl Alcohol
Grip Length:	0.157 Inches Minimum And 0.219 Inches Maximum
Width Across Flats:	0.244 Inches Minimum And 0.250 Inches Maximum
Material:	Iron Alloy 660 Boltiron Alloy 660 Nutiron Alloy 660 Sleeve
Material Document And Classification:	Ams 5735 Assn Std Single Material Response Bolt Or Ams 5737 Assn Std Single Material Response Boltams 5735 Assn Std Single Material Response Nut Or Ams 5737 Assn Std Single Material Response Nutams 5735 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve
Surface Treatment:	Passivate Boltpassivate Nutpassivate Sleeve
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Boltmil-s-5002 Mil Spec Single Treatment Response Nutmil-s-5002 Mil Spec Single Treatment Response Sleeve

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1671-08L3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.