

**Description**

Head Width: 1/4", Jo-bolt, NAS1671 series

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS167108L3
Minimum Qty (MOQ):	5
NSN:	5320-00-820-7283
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



## P/N NAS1671-08L3 Specifications

<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.096 Inches Maximum
<b>Shank Diameter:</b>	0.1625 Inches Minimum And 0.1645 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Expansion Device:</b>	Threaded Stem
<b>Lubrication:</b>	Wax Or Cetyl Alcohol
<b>Grip Length:</b>	0.157 Inches Minimum And 0.219 Inches Maximum
<b>Width Across Flats:</b>	0.244 Inches Minimum And 0.250 Inches Maximum
<b>Material:</b>	Iron Alloy 660 Boltiron Alloy 660 Nutiron Alloy 660 Sleeve
<b>Material Document And Classification:</b>	Ams 5735 Assn Std Single Material Response Bolt Or Ams 5737 Assn Std Single Material Response Boltams 5735 Assn Std Single Material Response Nut Or Ams 5737 Assn Std Single Material Response Nutams 5735 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve
<b>Surface Treatment:</b>	Passivate Boltpassivate Nutpassivate Sleeve
<b>Surface Treatment Document And Classification:</b>	Mil-s-5002 Mil Spec Single Treatment Response Boltmil-s-5002 Mil Spec Single Treatment Response Nutmil-s-5002 Mil Spec Single Treatment Response Sleeve

## How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1671-08L3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.