



Military-Fasteners.com

P/N NAS1671-3L11

## Description

Head Width: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS16713L11
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-049-9229
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1671-3L11 Specifications

<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.113 Inches Maximum
<b>Shank Diameter:</b>	0.197 Inches Minimum And 0.199 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Expansion Device:</b>	Threaded Stem
<b>Grip Length:</b>	0.657 Inches Minimum And 0.719 Inches Maximum
<b>Width Across Flats:</b>	0.305 Inches Minimum And 0.312 Inches Maximum
<b>Hardness Rating:</b>	30.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas1671 Professional/Industrial Association Standard

## How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1671-3L11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.