

Description

Head Width: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS16713L8
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-818-6621
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS1671-3L8 Specifications

Head Style:	Hexagon
Head Height:	0.113 Inches Maximum
Shank Diameter:	0.1970 Inches Minimum And 0.1990 Inches Maximum
Expansion Device:	Threaded Stem
Lubrication:	Wax Or Cetyl Alcohol
Grip Length:	0.470 Inches Minimum And 0.531 Inches Maximum
Width Across Flats:	0.305 Inches Minimum And 0.312 Inches Maximum
Material:	Iron Alloy 660 Boltiron Alloy 660 Nutiron Alloy 660 Sleeve
Material Document And Classification:	Ams 5735 Assn Std Single Material Response Bolt Or Ams 5737 Assn Std Single Material Response Boltams 5735 Assn Std Single Material Response Nut Or Ams 5737 Assn Std Single Material Response Nutams 5735 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve
Surface Treatment:	Passivate Boltpassivate Nutpassivate Sleeve
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec Single Treatment Response Boltmil-s-5002 Mil Spec Single Treatment Response Nutmil-s-5002 Mil Spec Single Treatment Response Sleeve

How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1671-3L8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.