

Description

Head Width: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|--------------------|------------------|
| SKU / Model: | NAS16713L8 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-00-818-6621 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS1671-3L8 Specifications

| | |
|---|--|
| Head Style: | Hexagon |
| Head Height: | 0.113 Inches Maximum |
| Shank Diameter: | 0.1970 Inches Minimum And 0.1990 Inches Maximum |
| Expansion Device: | Threaded Stem |
| Lubrication: | Wax Or Cetyl Alcohol |
| Grip Length: | 0.470 Inches Minimum And 0.531 Inches Maximum |
| Width Across Flats: | 0.305 Inches Minimum And 0.312 Inches Maximum |
| Material: | Iron Alloy 660 Boltiron Alloy 660 Nutiron Alloy 660 Sleeve |
| Material Document And Classification: | Ams 5735 Assn Std Single Material Response Bolt Or Ams 5737 Assn Std Single Material Response Boltams 5735 Assn Std Single Material Response Nut Or Ams 5737 Assn Std Single Material Response Nutams 5735 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve |
| Surface Treatment: | Passivate Boltpassivate Nutpassivate Sleeve |
| Surface Treatment Document And Classification: | Mil-s-5002 Mil Spec Single Treatment Response Boltmil-s-5002 Mil Spec Single Treatment Response Nutmil-s-5002 Mil Spec Single Treatment Response Sleeve |

How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1671-3L8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.