

Description

Thread Size: 3/16", Head Width: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS16714L4
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-188-1598
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1671-4L4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Head Style:	Hexagon
Head Height:	0.135 Inches Maximum
Shank Diameter:	0.258 Inches Minimum And 0.260 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Expansion Device:	Threaded Stem
Grip Length:	0.220 Inches Minimum And 0.281 Inches Maximum
Width Across Flats:	0.367 Inches Minimum And 0.375 Inches Maximum
Thread Quantity Per Inch:	32
Hardness Rating:	30.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Nominal Thread Size:	0.190 Inches
Shear Strength:	7200 Double Pounds Per Square Inch
Special Features:	Self-locking
Material:	Titanium Alloy Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1671 Professional/Industrial Association Standard

How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1671-4L4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.