

Description

Thread Size: 3/16", Head Width: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS16714L4 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5320-00-188-1598 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |



* See page 2 for technical characteristics

P/N NAS1671-4L4 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Head Style: | Hexagon |
| Head Height: | 0.135 Inches Maximum |
| Shank Diameter: | 0.258 Inches Minimum And 0.260 Inches Maximum |
| Shank Style: | Threaded Self-plugging Shank W/sleeve |
| Expansion Device: | Threaded Stem |
| Grip Length: | 0.220 Inches Minimum And 0.281 Inches Maximum |
| Width Across Flats: | 0.367 Inches Minimum And 0.375 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | 30.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall |
| Nominal Thread Size: | 0.190 Inches |
| Shear Strength: | 7200 Double Pounds Per Square Inch |
| Special Features: | Self-locking |
| Material: | Titanium Alloy Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas1671 Professional/industrial Association Standard |

How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1671-4L4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.