

Description

Fastener Length: 33/64", Head Width: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS16714L6
Minimum Qty (MOQ):	1 EA
NSN:	5320-00-841-6827
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1671-4L6 Specifications

Fastener Length:	0.491 Inches Minimum And 0.521 Inches Maximum
Head Style:	Hexagon
Head Height:	0.125 Inches Minimum And 0.135 Inches Maximum
Shank Diameter:	0.258 Inches Minimum And 0.260 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film Or Paraffin Wax
Grip Length:	0.344 Inches Minimum And 0.406 Inches Maximum
Width Across Flats:	0.367 Inches Minimum And 0.375 Inches Maximum
Hardness Rating:	30.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Material:	Iron Alloy 660 Bolt
Material:	Iron Alloy 660 Nut
Material:	Iron Alloy 660 Sleeve
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Bolt Or Ams 5732 Assn Std Single Material Response Bolt Or Ams 5737 Assn Std Single Material Response Bolt
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5737 Assn Std Single Material Response Nut
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Sleeve Or Ams 5732 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve
Surface Treatment:	Passivate Bolt
Surface Treatment:	Passivate Nut
Surface Treatment:	Passivate Sleeve
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Bolt
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Nut
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Sleeve

How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1671-4L6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.