

Description

Fastener Length: 37/64", Head Width: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS16714L7
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-802-7173
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1671-4L7 Specifications

<b>Fastener Length:</b>	0.554 Inches Minimum And 0.584 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.125 Inches Minimum And 0.135 Inches Maximum
<b>Shank Diameter:</b>	0.258 Inches Minimum And 0.260 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film Or Paraffin Wax
<b>Grip Length:</b>	0.406 Inches Minimum And 0.469 Inches Maximum
<b>Width Across Flats:</b>	0.367 Inches Minimum And 0.375 Inches Maximum
<b>Hardness Rating:</b>	30.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
<b>Material:</b>	Iron Alloy 660 Bolt
<b>Material:</b>	Iron Alloy 660 Nut
<b>Material:</b>	Iron Alloy 660 Sleeve
<b>Material Document And Classification:</b>	Ams 5735 Assn Std Single Material Response Bolt Or Ams 5737 Assn Std Single Material Response Bolt
<b>Material Document And Classification:</b>	Ams 5735 Assn Std Single Material Response Nut Or Ams 5737 Assn Std Single Material Response Nut
<b>Material Document And Classification:</b>	Ams 5735 Assn Std Single Material Response Sleeve Or Ams 5737 Assn Std Single Material Response Sleeve

## How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1671-4L7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.