

**Description**

Fastener Length: 41/64", Head Width: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS16714L8
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-857-0661
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE  
AVAILABLE

## P/N NAS1671-4L8 Specifications

<b>Fastener Length:</b>	0.616 Inches Minimum And 0.646 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.125 Inches Minimum And 0.135 Inches Maximum
<b>Shank Diameter:</b>	0.258 Inches Minimum And 0.260 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Expansion Device:</b>	Serrated Stem-type W
<b>Lubrication:</b>	Dry Film Or Paraffin Wax
<b>Grip Length:</b>	0.469 Inches Minimum And 0.531 Inches Maximum
<b>Width Across Flats:</b>	0.367 Inches Minimum And 0.375 Inches Maximum
<b>Hardness Rating:</b>	30.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
<b>Shear Strength:</b>	7200 Double Pounds Per Square Inch
<b>Material:</b>	Iron Alloy 660 Sleeve
<b>Material:</b>	Iron Alloy 660 Stem
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Stem
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Sleeve
<b>Surface Treatment:</b>	Silver Stem
<b>Surface Treatment:</b>	Passivate Sleeve
<b>Surface Treatment Document And Classification:</b>	Mil-s-5002 Mil Spec 1st Treatment Response Sleeve
<b>Specification/standard Data:</b>	80205-nas1671 Professional/Industrial Association Standard

## How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1671-4L8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.