

Description

Fastener Length: 41/64", Head Width: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS16714L8
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-857-0661
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1671-4L8 Specifications

Fastener Length:	0.616 Inches Minimum And 0.646 Inches Maximum
Head Style:	Hexagon
Head Height:	0.125 Inches Minimum And 0.135 Inches Maximum
Shank Diameter:	0.258 Inches Minimum And 0.260 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Expansion Device:	Serrated Stem-type W
Lubrication:	Dry Film Or Paraffin Wax
Grip Length:	0.469 Inches Minimum And 0.531 Inches Maximum
Width Across Flats:	0.367 Inches Minimum And 0.375 Inches Maximum
Hardness Rating:	30.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Shear Strength:	7200 Double Pounds Per Square Inch
Material:	Iron Alloy 660 Sleeve
Material:	Iron Alloy 660 Stem
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Stem
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Sleeve
Surface Treatment:	Silver Stem
Surface Treatment:	Passivate Sleeve
Surface Treatment Document And Classification:	Mil-s-5002 Mil Spec 1st Treatment Response Sleeve
Specification/standard Data:	80205-nas1671 Professional/Industrial Association Standard

How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1671-4L8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.