

Description

Fastener Length: 1-29/64", Head Width: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS16714L9
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-036-9241
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



\* See page 2 for technical characteristics

## P/N NAS1671-4L9 Specifications

<b>Fastener Length:</b>	1.429 Inches Minimum And 1.459 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.135 Inches Nominal
<b>Shank Diameter:</b>	0.258 Inches Minimum And 0.260 Inches Maximum
<b>Shank Style:</b>	Threaded Self-plugging Shank W/sleeve
<b>Expansion Device:</b>	Threaded Mandrel
<b>Grip Length:</b>	0.594 Inches Nominal
<b>Width Across Flats:</b>	0.367 Inches Minimum And 0.375 Inches Maximum
<b>Material:</b>	Iron Alloy 660 Overall
<b>Surface Treatment:</b>	Passivate Overall

## How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1671-4L9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.