

Description

Fastener Length: 1-29/64", Head Width: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS16714L9
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-036-9241
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N NAS1671-4L9 Specifications

Fastener Length:	1.429 Inches Minimum And 1.459 Inches Maximum
Head Style:	Hexagon
Head Height:	0.135 Inches Nominal
Shank Diameter:	0.258 Inches Minimum And 0.260 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Expansion Device:	Threaded Mandrel
Grip Length:	0.594 Inches Nominal
Width Across Flats:	0.367 Inches Minimum And 0.375 Inches Maximum
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall

How to Order

Order this jo-bolt from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1671-4L9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.