

Description

Fastener Length: 39/64", Head Width: 7/16", jo bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS16715L7
Minimum Qty (MOQ):	1
NSN:	5320-00-476-7626
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N NAS1671-5L7 Specifications

Fastener Length:	0.579 Inches Minimum And 0.609 Inches Maximum
Head Style:	Hexagon
Head Height:	0.160 Inches Maximum
Shank Diameter:	0.310 Inches Minimum And 0.312 Inches Maximum
Shank Style:	Threaded Self-plugging Shank W/sleeve
Expansion Device:	Threaded Mandrel
Grip Length:	0.407 Inches Minimum And 0.469 Inches Maximum
Width Across Flats:	0.429 Inches Minimum And 0.437 Inches Maximum
Hardness Rating:	30.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Shear Strength:	10350 Double Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5735 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data:	80205-nas1671 Professional/industrial Association Standard

How to Order

Order this blind rivet from our inventory online by visiting <https://military-fasteners.com/rivets/blind+rivets/NAS1671-5L7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.