

P/N NAS1674-3L5

Description

NAS1674 series rivet

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS16743L5

Minimum Qty (MOQ):

NSN: 5320-00-928-0327

ECCN: EAR99

National Motor Freight: 013630, Alum Rivets









^{*} See page 2 for technical characteristics

P/N NAS1674-3L5 Specifications

Fast ner Length: 0.481 Inches Minimum And 0.511 Inches Maximum Head Style: Hexagon Countersunk Head Height: 0.197 Inches Minimum And 0.079 Inches Maximum Shank Diameter: 0.197 Inches Minimum And 0.199 Inches Maximum Shank Style: Threaded Self-plugging Shank W/sleeve Expansion Device: Threaded Stem Grip Length: 0.322 Inches Minimum And 0.344 Inches Maximum Width Across Flats: 0.322 Inches Minimum And 0.346 Inches Maximum Hardness Rating: 0.322 Inches Minimum Bolt And 43.0 Rockwell C Maximum Bolt Countersink Angle: 9.9. Degrees Minimum And 101.0 Degrees Maximum Material: 4 Imminum Alloy 7075 Nut Material: 4 Imminum Alloy 7075 Nut Material: 5 keel Comp 304 Sleeve Or Steel Comp 303 Sleeve Or Steel Comp 303' Sleeve Material Document And Classification: 6 keel Comp 304 Sleeve Or Steel Comp 303 Sleeve Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Spec Single Material Response Nut Material Document And Classification: 0.49-2259 Fed Spec Single Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Assn 5642 Assn Std 3rd Material Response Sleeve Or Assn 5641 Assn Std 3rd Material Response Sleeve Or Ass		
Head Height: 0.072 Inches Minimum And 0.079 Inches Maximum Shank Diameter: 0.197 Inches Minimum And 0.199 Inches Maximum Shank Style: Threaded Self-plugging Shank Wisleeve Threaded Stem O.282 Inches Minimum And 0.344 Inches Maximum And 0.344 Inches Maximum And 0.345 Inches Minimum Bolt And 3.0 Rockwell C Maximum Bolt Andreas Rating: 0.39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt Andreas Rating: 0.90.0 Degrees Minimum And 10.10 Degrees Maximum Anderial: 0.4 Uminimum Alloy 7075 Nut Anderial: 0.4 Uminimum Alloy 7075 Self Comp 303 Sleeve Or Steel Comp 303 Sleeve Anderial: 0.4 Uminimum Alloy 7075 Self Comp 303 Sleeve Or Steel Comp 303 Sleeve Anderial Document And Classification: 0.4 Case Self-Self Mils Sec 1st Material Response Bolt Or Mils-6049 Mi	Fastener Length:	0.481 Inches Minimum And 0.511 Inches Maximum
Shank Diameter: 0.197 Inches Minimum And 0.199 Inches Maximum Shank Style: Threaded Self-plugging Shank W/sleeve Expansion Device: Threaded Stem Grip Length: 0.282 Inches Minimum And 0.344 Inches Maximum Width Across Flats: 0.332 Inches Minimum And 0.346 Inches Maximum Hardness Rating: 39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Material: Aluminum Alloy 7075 Nut Material: Steel Comp 4140 Bolt or Steel Comp 304 Sleeve Or Steel Comp 4130 Bolt Material Document And Classification: Mill-s-5626 Mill Spec 1st Material Response Bolt Or Mill-s-6049 Mill Spec 2nd Material Response Bolt Or Mill-s-6758 Mill Spec 3rd Material Response Bolt Or Mill-s-6049 Mill Spec 2nd Material Response Bolt Or Mill-s-6758 Mill Spec 3rd Material Response Material Response Sleeve Or Ams 5639 Assn Std 1st Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material R	Head Style:	Hexagon Countersunk
Shank Style: Threaded Self-plugging Shank W/sleeve Expansion Device: Threaded Stem Grip Length: 0.282 Inches Minimum And 0.344 Inches Maximum Width Across Flats: 0.332 Inches Minimum And 0.346 Inches Maximum Hardness Rating: 39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Material: Aluminum Alloy 7075 Nut Material: Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt Material Document And Classification: Steel Comp 304 Sleeve Or Steel Comp 303 Sleeve Or Steel Comp 303f Sleeve Material Document And Classification: Oq-s-763 Fed Spec Single Material Response Bolt Or Mili-s-6049 Mil Spec 2nd Material Response Bolt Or Mili-s-6758 Mil Spec 3rd Material Response Bolt or Mili-s-6758 Fed Spec Single Material Response Sleeve Or Ams 5639 Assn 5td 1st Material Response Sleeve Or Assn 5631 Assn 5td 3rd Material Response Sleeve Or Assn 5641 Assn 5td 3rd Material Response Sleeve Or Ams 5641 Assn 5td 3rd Material Response Sleeve Or Ams 5641 Assn 5td 3rd Material Response Sleeve Or Ams 5641 Assn 5td 3rd Material Response Sleeve Or Ams 5641 Assn 5td 3rd Material Response Sleeve Or Ams 5641 Assn 5td 3rd Material Response Sleeve Or Ams 5641 Assn 5td 3rd Material Response Sleeve Or Ams 5641 Assn 5td 3rd Material Response Sleeve Or Ams 5641 Assn 5td 3rd Material Response Sleeve Or Ams 5641 Assn 5td 3rd Material Response Sleeve Or Ams 5641 Assn 5td 3rd Material Response Sleeve Or Ams 5641 Assn 5td 3rd Material Response Sleeve Or Ams	Head Height:	0.072 Inches Minimum And 0.079 Inches Maximum
Expansion Device: Threaded Stem Grip Length: 0.282 Inches Minimum And 0.344 Inches Maximum Width Across Flats: 0.332 Inches Minimum And 0.346 Inches Maximum Hardness Rating: 39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Material: 40.0 Mumimum Albot 7075 Nut Material: 51.0 Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt Material: 51.0 Steel Comp 304 Sleeve Or Steel Comp 8740 Bolt Or Steel Comp 303f Sleeve Material Document And Classification: 61.0 Steel Comp 304 Sleeve Or Steel Comp 303f Sleeve Material Document And Classification: 70.4-2-225/9 Fed Spec Single Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Nut Material Document And Classification: 70.4-2-225/9 Fed Spec Single Material Response Sleeve Or Ams 5639 Assn Std 1st Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Astm 5641 Assn Std 3rd Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Astm 5641 Assn Std 3rd Material Response Sleeve Surface Treatment: 50.0 Cadmium Bolt And Chromate Bolt Surface Treatment Document And 61.0 Assn Std 3rd Material Response Nut Surface Treatment Document And 70.0 Assn Std 3rd Material Response Nut Classification: 50.0 Assn Std 3rd Assn Std 3rd Assn Std 3rd Assn Std 3rd Material Response Sleeve And Passivate Sleeve Surface Treatment Document And 70.0 Assn Std 3rd Material Response Nut Surface Treatment Document And 70.0 Assn Std 3rd Material Response Sleeve And Passivate S	Shank Diameter:	0.197 Inches Minimum And 0.199 Inches Maximum
Grip Length: Width Across Flats: 0.332 Inches Minimum And 0.344 Inches Maximum Hardness Rating: 39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt Countersink Angle: 99.0 Degrees Minimum And 10.1.0 Degrees Maximum Material: Aluminum Alloy 7075 Nut Material: Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt Material: Steel Comp 304 Sleeve Or Steel Comp 303 Sleeve Or Steel Comp 303 Fleeve Material Document And Classification: Response Bolt Material Document And Classification: Qq-a-225/9 Fed Spec Single Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Bolt Material Document And Classification: Qq-a-225/9 Fed Spec Single Material Response Nut Material Document And Classification: Aluminum Alloy 7075 Fed Spec 1st Material Response Sleeve Or Ams 5639 Assn Std 1st Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Surface Treatment: Cadmium Bolt And Chromate Bolt Surface Treatment Document And Classification: Surface Treatment Document And Classification: Qq-a-416.ty 2.cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve Qq-a-416.ty 2.cl 2 Fed Spec Single Treatment Response Bolt Classification: Surface Treatment Document And Classification: Qq-a-416.ty 2.cl 2 Fed Spec Single Treatment Response Bolt	Shank Style:	Threaded Self-plugging Shank W/sleeve
Width Across Flats: 0.332 Inches Minimum And 0.346 Inches Maximum Hardness Rating: 39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Material: Aluminum Alloy 7075 Nut Material: Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt Material: Steel Comp 304 Sleeve Or Steel Comp 303 Sleeve Material Document And Classification: Mil-5-5626 Mil Spec 1st Material Response Bolt Or Mil-5-6049 Mil Spec 2nd Material Response Bolt Or Mil-5-6758 Mil Spec 3rd Material Material Document And Classification: Qq-2-225/9 Fed Spec Single Material Response Nut Material Document And Classification: Qq-5-763 Fed Spec 1st Material Response Sleeve Or Ams 5639 Assn Std 1st Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Assn 5641 Assn Std 3rd Material Response Sleeve Surface Treatment: Cadmium Bolt And Chromate Bolt Surface Treatment Document And Classification: Cadmium Sleeve And Chromate Sleeve And Passivate Sleeve Surface Treatment Document And Classification: Q-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Tre	Expansion Device:	Threaded Stem
Hardness Rating: 39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Material: Aluminum Alloy 7075 Nut Material: Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt Material: Steel Comp 304 Sleeve Or Steel Comp 303 Sleeve Or Steel Comp 303 Sleeve Material Document And Classification: Response Bolt Milis-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Mut Material Document And Classification: Qq-a-225/9 Fed Spec Single Material Response Nut Material Document And Classification: Qq-s-763 Fed Spec 1st Material Response Sleeve Or Ams 5649 Assn 5td 3rd Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn 5td 3rd Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn 5td 3rd Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Surface Treatment: Cadmium Bolt And Chromate Bolt Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt	Grip Length:	0.282 Inches Minimum And 0.344 Inches Maximum
Countersink Angle:99.0 Degrees Minimum And 101.0 Degrees MaximumMaterial:Aluminum Alloy 7075 NutMaterial:Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 BoltMaterial:Steel Comp 304 Sleeve Or Steel Comp 303 Sleeve Or Steel Comp 303f SleeveMaterial Document And Classification:Mils-s-5626 Mil Spec 1st Material Response Bolt Or Mils-6049 Mil Spec 2nd Material Response Bolt Or Mils-6758 Mil Spec 3rd Material Response Bolt Or Mils-6049 Mil Spec 2nd Material Response Bolt Or Mils-6758 Mil Spec 3rd Material Response Bolt Or Mils-6049 Mil Spec 2nd Material Response Bolt Or Mils-6758 Mil Spec 3rd Material Response MutMaterial Document And Classification:Qq-a-225/9 Fed Spec Single Material Response Sleeve Or Ams 5639 Assn Std 1st Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response SleeveSurface Treatment:Anodize NutSurface Treatment Document And Classification:Cadmium Sleeve And Chromate Sleeve And Passivate SleeveSurface Treatment Document And Classification:Mils-8625,ty 2 Mil Spec Single Treatment Response NutSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response SleeveSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt	Width Across Flats:	0.332 Inches Minimum And 0.346 Inches Maximum
Material:Aluminum Alloy 7075 NutMaterial:Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 BoltMaterial:Steel Comp 304 Sleeve Or Steel Comp 303 Sleeve Or Steel Comp 303f SleeveMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd MaterialMaterial Document And Classification:Qq-a-225/9 Fed Spec Single Material Response NutMaterial Document And Classification:Qq-s-763 Fed Spec 1st Material Response Sleeve Or Ams 5639 Assn Std 1st Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response SleeveSurface Treatment:Anodize NutSurface Treatment:Cadmium Bolt And Chromate BoltSurface Treatment Document And Classification:Mil-a-8625,ty 2 Mil Spec Single Treatment Response NutSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response SleeveSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt	Hardness Rating:	39.0 Rockwell C Minimum Bolt And 43.0 Rockwell C Maximum Bolt
Material:Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 BoltMaterial:Steel Comp 304 Sleeve Or Steel Comp 303 Sleeve Or Steel Comp 303f SleeveMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response BoltMaterial Document And Classification:Qq-a-225/9 Fed Spec Single Material Response NutMaterial Document And Classification:Qq-s-763 Fed Spec 1st Material Response Sleeve Or Ams 5639 Assn Std 1st Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response SleeveSurface Treatment:Anodize NutSurface Treatment:Cadmium Bolt And Chromate BoltSurface Treatment Document And Classification:Cadmium Sleeve And Chromate Sleeve And Passivate SleeveSurface Treatment Document And Classification:Mil-a-8625,ty 2 Mil Spec Single Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response SleeveSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Bolt	Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:Steel Comp 304 Sleeve Or Steel Comp 303 Sleeve Or Steel Comp 303 SleeveMaterial Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Material Response Sleeve Or Ams 5639 Assn Std 1st Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response SleeveSurface Treatment:Anodize NutSurface Treatment Document And Classification:Cadmium Bolt And Chromate Sleeve And Passivate SleeveSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response SleeveSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt	Material:	Aluminum Alloy 7075 Nut
Material Document And Classification:Mil-s-5626 Mil Spec 1st Material Response Bolt Or Mil-s-6049 Mil Spec 2nd Material Response Bolt Or Mil-s-6758 Mil Spec 3rd Material Response BoltMaterial Document And Classification:Qq-a-225/9 Fed Spec Single Material Response NutMaterial Document And Classification:Qq-s-763 Fed Spec 1st Material Response Sleeve Or Ams 5639 Assn Std 1st Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response SleeveSurface Treatment:Anodize NutSurface Treatment:Cadmium Bolt And Chromate BoltSurface Treatment Document And Classification:Cadmium Sleeve And Chromate Sleeve And Passivate SleeveSurface Treatment Document And Classification:Mil-a-8625,ty 2 Mil Spec Single Treatment Response NutSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response SleeveSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt	Material:	Steel Comp 4140 Bolt Or Steel Comp 8740 Bolt Or Steel Comp 4130 Bolt
Material Document And Classification:Response BoltMaterial Document And Classification:Qq-a-225/9 Fed Spec Single Material Response NutMaterial Document And Classification:Qq-s-763 Fed Spec 1st Material Response Sleeve Or Ams 5639 Assn Std 1st Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response SleeveSurface Treatment:Anodize NutSurface Treatment:Cadmium Bolt And Chromate BoltSurface Treatment Document And Classification:Cadmium Sleeve And Chromate Sleeve And Passivate SleeveSurface Treatment Document And Classification:Mil-a-8625,ty 2 Mil Spec Single Treatment Response NutSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response SleeveSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt	Material:	Steel Comp 304 Sleeve Or Steel Comp 303 Sleeve Or Steel Comp 303f Sleeve
Material Document And Classification:Qq-s-763 Fed Spec 1st Material Response Sleeve Or Ams 5639 Assn Std 1st Material Response Sleeve Or Astm A582 Assn Std 2nd Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response SleeveSurface Treatment:Anodize NutSurface Treatment:Cadmium Bolt And Chromate BoltSurface Treatment Document And Classification:Cadmium Sleeve And Chromate Sleeve And Passivate SleeveSurface Treatment Document And Classification:Mil-a-8625,ty 2 Mil Spec Single Treatment Response NutSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response SleeveSurface Treatment Document And Classification:Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt	Material Document And Classification:	
Material Document And Classification: Material Response Sleeve Or Ams 5641 Assn Std 3rd Material Response Sleeve Surface Treatment: Anodize Nut Cadmium Bolt And Chromate Bolt Surface Treatment: Cadmium Sleeve And Chromate Sleeve And Passivate Sleeve Surface Treatment Document And Classification: Surface Treatment Document And Classification: Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Bolt Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt	Material Document And Classification:	Qq-a-225/9 Fed Spec Single Material Response Nut
Surface Treatment: Surface Treatment: Cadmium Bolt And Chromate Bolt Surface Treatment: Cadmium Sleeve And Chromate Sleeve And Passivate Sleeve Surface Treatment Document And Classification: Surface Treatment Document And Classification: Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt	Material Document And Classification:	
Surface Treatment Document And Classification: Cadmium Sleeve And Chromate Sleeve And Passivate Sleeve Mil-a-8625,ty 2 Mil Spec Single Treatment Response Nut Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt	Surface Treatment:	Anodize Nut
Surface Treatment Document And Classification: Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt	Surface Treatment:	Cadmium Bolt And Chromate Bolt
Classification: Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt	Surface Treatment:	Cadmium Sleeve And Chromate Sleeve And Passivate Sleeve
Classification: Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve		Mil-a-8625,ty 2 Mil Spec Single Treatment Response Nut
Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt		Qq-p-416,ty 2,cl 2 Fed Spec 1st Treatment Response Sleeve And Qq-p-35 Fed Spec 2nd Treatment Response Sleeve
Specification/standard Data: 80205-nas1674 Professional/industrial Association Standard		Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Bolt
	Specification/standard Data:	80205-nas1674 Professional/industrial Association Standard

How to Order

