

Description

Hole Diameter: 17/64", NAS1676 series washer

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information****Alternate Part Numbers**[NAS1676-C416](#)

SKU / Model:	NAS1676C416
Minimum Qty (MOQ):	50
NSN:	5310-00-262-3562
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N NAS1676C416 Specifications

Hole Diameter:	0.255 Inches Minimum And 0.267 Inches Maximum
Outside Diameter:	0.363 Inches Nominal
Material Thickness:	0.078 Inches Nominal
End Item Identification:	Mrap Rg-33
Hardness Rating:	35.0 Rockwell C Minimum And 43.0 Rockwell C Maximum
Material:	Steel Comp 301 Overall Or Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 303se Overall Or Steel Comp 304 Overall Or Steel Comp 304l Overall Or Steel Comp 305 Overall Or Steel Comp 308 Overall Or Steel Comp 309 Overall Or Steel Comp 309s Overall Or Steel Comp 310 Overall Or Steel Comp 310s Overall Or Steel Comp 314 Overall Or Steel Comp 316 Overall Or Steel Comp 316l Overall Or Steel Comp 317 Overall Or Steel Comp 321 Overall Or Steel Comp 347 Overall Or Steel Comp 385 Overall Or Steel Comp 302 Overall Or Steel Comp 384 Overall Or Steel Comp 348 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Style Designator:	Split Helical-right Hand
Specification/standard Data:	80205-nas1676 Professional/industrial Association Standard
Nondefinitive Spec/std Data:	C Class
Departure From Cited Designator:	As Modified By Dim.

How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/NAS1676C416> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.