

Description

NAS1676C8 Lock Washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1676C8                                 |
| Minimum Qty (MOQ):      | 100                                       |
| NSN:                    | 5310-00-455-2672                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



\* See page 2 for technical characteristics

# P/N NAS1676C8 Specifications

|  |  |
|--|--|
| Hole Diameter:                                 | 0.168 Inches Minimum And 0.175 Inches Maximum              |
| Outside Diameter:                              | 0.267 Inches Maximum                                       |
| Material Thickness:                            | 0.047 Inches Minimum                                       |
| Hardness Rating:                               | 35.0 Rockwell C Minimum And 45.0 Rockwell C Maximum        |
| Material:                                      | Steel Corrosion Resisting Overall                          |
| Surface Treatment:                             | Passivate Overall  |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall         |
| Style Designator:                              | Split Helical-right Hand                                   |
| Specification/standard Data:                   | 80205-nas1676 Professional/industrial Association Standard |

## How to Order

Order this lock washer from our inventory online by visiting <https://military-fasteners.com/washers/lock+washers/NAS1676C8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.