

Description

Length: 4-3/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1677C21W44N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-350-0096
Schedule B:	3926.90.9995
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS1677C21W44N Specifications

Overall Length:	4.758 Inches Nominal
Overall Width:	0.500 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Distance Between Mounting Hole Centers:	4.320 Inches Nominal
Cushioning Material:	Rubber, Synthetic, Ams 3209
Cushion:	Included
Mounting Pad:	Not Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	1.297 Inches Minimum And 1.327 Inches Maximum
Inside Diameter/arch Length:	3.485 Inches Minimum And 3.515 Inches Maximum
Special Features:	Cushioned Bridge With Wedge Included
Material:	Steel, Mil-s-5059, Comp 302 Or Steel, Ams 5510
Material:	Steel Comp 302 Or Steel Comp 321
Surface Treatment:	Passivate
Style Designator:	Straight Arch
Surface Treatment:	Passivated, Qq-p-35
Specification/standard Data:	80205-nas1677 Professional/Industrial Association Standard

How to Order

Order this cushioned retaining strap from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677C21W44N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.