

**Description**

Length: 4-3/4"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1677C21W44N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-350-0096
Schedule B:	3926.90.9995
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1677C21W44N Specifications

<b>Overall Length:</b>	4.758 Inches Nominal
<b>Overall Width:</b>	0.500 Inches Nominal
<b>Material Thickness:</b>	0.032 Inches Nominal
<b>Distance Between Mounting Hole Centers:</b>	4.320 Inches Nominal
<b>Cushioning Material:</b>	Rubber, Synthetic, Ams 3209
<b>Cushion:</b>	Included
<b>Mounting Pad:</b>	Not Included
<b>Mounting Hole Size:</b>	0.204 Inches Nominal
<b>Distance Between Base And Inside Of Arch:</b>	1.297 Inches Minimum And 1.327 Inches Maximum
<b>Inside Diameter/arch Length:</b>	3.485 Inches Minimum And 3.515 Inches Maximum
<b>Special Features:</b>	Cushioned Bridge With Wedge Included
<b>Material:</b>	Steel, Mil-s-5059, Comp 302 Or Steel, Ams 5510
<b>Material:</b>	Steel Comp 302 Or Steel Comp 321
<b>Surface Treatment:</b>	Passivate
<b>Style Designator:</b>	Straight Arch
<b>Surface Treatment:</b>	Passivated, Qq-p-35
<b>Specification/standard Data:</b>	80205-nas1677 Professional/Industrial Association Standard

## How to Order

Order this cushioned retaining strap from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677C21W44N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.