

Description

Length: 3-3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1677C22W36N
Minimum Qty (MOQ):	5 EA
NSN:	5340-01-395-1063
Schedule B:	7318.29.0000
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS1677C22W36N Specifications

Overall Length:	3.808 Inches Nominal
Overall Width:	0.500 Inches Nominal
Material Thickness:	0.032 Inches Nominal
Distance Between Mounting Hole Centers:	3.040 Inches Minimum And 3.100 Inches Maximum
Cushioning Material:	Rubber, Synthetic
Cushion:	Included
Mounting Pad:	Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	1.360 Inches Minimum And 1.390 Inches Maximum
Inside Diameter/arch Length:	2.235 Inches Minimum And 2.265 Inches Maximum
Material:	Steel, Corrosion Resisting
Material:	Steel Corrosion Resisting
Surface Treatment:	Passivate
Style Designator:	Tapered Arch
Surface Treatment:	Passivated, Qq-p-35
Specification/standard Data:	80205-nas1677c22w36n Professional/Industrial Association Standard

How to Order

Order this cushioned retaining strap from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677C22W36N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.