

## **P/N NAS1677D10W20N**

## **Description**

Length: 2-17/32"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1677D10W20N

Minimum Qty (MOQ): 5 EA

NSN: 5340-01-615-3205

Schedule B: 7616.10.1000

ECCN: 9A991

National Motor Freight: 157170, Plastic / Rubr Straps / Rope / Cord / Strip



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1677D10W20N Specifications

Overall Length:	2.538 Inches Nominal
Overall Width:	0.500 Inches Nominal
Material Thickness:	0.051 Inches Nominal
Distance Between Mounting Hole Centers:	2.040 Inches Minimum And 2.100 Inches Maximum
End Item Identification:	F/a-18 E/f
Cushioning Material:	Rubber, Synthetic, Ams 3209
Cushion:	Included
Mounting Pad:	Included
Mounting Hole Size:	0.204 Inches Nominal
Distance Between Base And Inside Of Arch:	0.766 Inches Minimum And 0.796 Inches Maximum
Inside Diameter/arch Length:	1.235 Inches Minimum And 1.265 Inches Maximum
Material:	Aluminum Alloy, 2024, T4
Material:	Aluminum Alloy 2024
Style Designator:	Saddle Arch

### **How to Order**

Order this cushioned retaining strap from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D10W20N">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1677D10W20N</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.